



## PB 910AF

Black MB

### Description

- Product: Black Master-Batch
- Carrier: Poly Ethylene
- Active ingredient: Carbon Black

### Application & Addition Rate

- PE Garbage Bag, PE Shopping Bag: 2 to 5%
- PE Mulch Film: 2 to 6%
- PE/PP Sheet: 1 to 3%
- PE/PP Molding (Injection, Blow, Rotational): 1 to 3%

### Advantages

- Excellent Dispersion
- High Opacity
- Good Light and Heat Stability

### Typical Properties

|          | Properties                     | Test method | Value   | Unit              |
|----------|--------------------------------|-------------|---------|-------------------|
| Physical | Melt Flow Rate (190°C/21.6 Kg) | ASTM D 1238 | 25      | g/10min           |
|          | Carbon Black Content           | ASTM D 4218 | 45 ± 1  | %                 |
|          | Density                        | ASTM D 1505 | 1.16    | g/cm <sup>3</sup> |
|          | Moisture                       | ASTM D 644  | Max 0.1 | %                 |

### Food Contact Status

- Not Approved.

### Storage & Packaging

- Store in dry place below 30 °C away from sun exposure not to exceed 12 months
- Packed in 25 kg PP raffia bags on 1250 kg stretch-wrapped pallet

#### NOTICE

2017-07

The information and data contained herein are believed to be correct and given in good faith, but because of the many particular factors which are outside our knowledge and control and affect the use of product, no warranty is given or is to be implied with respect to such information, nor do we offer any warranty of immunity against infringement.