# **CYPOL 926RS**

**Black MB** 

### **Description**

• Product: Black Master-Batch

Carrier: Poly Ethylene

Active ingredient: Carbon Black

## **Application & Addition Rate**

• PE Corrugated Sewage Pipe: 5 to 6%

Note: This grade is not recommended for High Pressure Pipe.

#### **Advantages**

- Good Dispersion
- Compatible Carrier
- Economical Grade

- Good Light and Heat Stability
- Wax & Lubricant Free

## **Typical Properties**

Properties		Test method	Value	Unit
Physical	Melt Flow Rate (190 °C/21.6 Kg)	ASTM D 1238	7 ± 5	g/10min
	Carbon Black Content	ASTM D 4218	40 ± 2	%
	Carbon Black Dispersion	ISIRI 7175-6	Max.3	-
	OIT(200°C)	PPTS	>20	min
	Density	ASTM D 1505	1.15	g/cm <sup>3</sup>
	Moisture	ASTM D 644	Max 0.1	%

#### Food Contact Status

Not approved

## Storage & Packaging

- Store in dry place below 30 °C away from sun exposure not to exceed 12 months
- Packed in 25 kg PP raffia bags on 1000 kg stretch-wrapped pallet

NOTICE

2017-0

The information and data contained herein are believed to be correct and given in good faith, but because of the many particular factors which are outside our knowledge and control and affect the use of product, no warranty is given or is to be implied with respect to such information, nor do we offer any warranty of immunity against infringement.