



## WMB 127M

White MB

### Description

- Product: White Master-Batch
- Carrier: Poly Olefin
- Active Ingredients: Treated Rutile TiO<sub>2</sub>

### Application & Addition Rate

- PE Film: 1 to 7%
- PE & PP Injection Molded Parts: 1 to 2%
- PE & PP Sheet: 1 to 3%

### Advantages

- Well Dispersed
- Excellent Hiding Power
- Exhibit Bluish Color Shade

### Typical Properties

|          | Properties                      | Test method | Value   | Unit              |
|----------|---------------------------------|-------------|---------|-------------------|
| Physical | Melt Flow Rate (190 °C/2.16 Kg) | ASTM D 1238 | 2       | g/10min           |
|          | Active Pigment Content          | ASTM D 4218 | 70 ± 2  |                   |
|          | Density                         | ASTM D 1505 | 1.9     | g/cm <sup>3</sup> |
|          | Moisture                        | ASTM D 644  | Max 0.1 | %                 |

### Food Contact Status

- Food contact approved ref. I.R.I Ministry of Health and Care. For more details please contact us.

### Storage & Packaging

- Store in dry place below 30 °C away from sun exposure not to exceed 12 months
- Packed in 25 kg PP raffia bags on 1250 kg stretch-wrapped pallet

NOTICE

2015-05

The information and data contained herein are believed to be correct and given in good faith, but because of the many particular factors which are outside our knowledge and control and affect the use of product, no warranty is given or is to be implied with respect to such information, nor do we offer any warranty of immunity against infringement.