



WMB 136

White MB

Description

- Product: White Master-Batch
- Carrier: Poly Styrene
- Active Ingredients: Treated Rutile TiO₂

Application & Addition Rate

- PS/ABS Injection Molded Parts: 1 to 3%
- PS Sheet Extrusion: 0.5 to 3

Advantages

- Easy Flow and High Processability
- Suitable Hiding Power
- High Quality RutileTiO₂
- Good Compatibility with both PS & ABS
- Bright White Shade
- Filler Free

Typical Properties

	Properties	Test method	Value	Unit
Physical	Melt Flow Rate (200 °C/5 Kg)	ASTM D 1238	20	g/10min
	Active Pigment Content	ASTM D 4218	55± 2	%
	Moisture	ASTM D 644	Max 0.1	%

Food Contact Status

- Food contact approved ref. I.R.I Ministry of Health and Care. For more details please contact us.

Storage & Packaging

- Store in dry place below 30 °C away from sun exposure not to exceed 12 months
- Packed in 25 kg PP raffia bags on 1250 kg stretch-wrapped pallet

NOTICE

2017-09

The information and data contained herein are believed to be correct and given in good faith, but because of the many particular factors which are outside our knowledge and control and affect the use of product, no warranty is given or is to be implied with respect to such information, nor do we offer any warranty of immunity against infringement.